## NSN 5305-00-019-1245

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-019-1245 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.258 inches and 0.357 inches **Fastener Length:** 0.375 inches **Head Style:** Round **Head Diameter:** Between 0.334 inches and 0.359 inches **Head Height:** Between 0.123 inches and 0.137 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.365 inches and 0.381 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.018 inches and 0.024 inches Material: Steel **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-00-019-1245

Assembled Washer Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0