NSN 5305-00-019-1678

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-019-1678 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.761 inches and 0.844 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Hexagon **Head Height:** Between 0.208 inches and 0.230 inches Width Between Flats: Between 0.489 inches and 0.500 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.567 inches and 0.590 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.028 inches and 0.034 inches **Special Features:** W/header point

Material:

Steel comp 1020 or steel comp 1050

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unf

NSN 5305-00-019-1678

Assembled Washer Screw - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0