NSN 5305-00-019-9461

Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-019-9461

Thread Direction: Right-hand Thread Length: Between 1.326 inches and 1.386 inches Fastener Length: Between 2.779 inches and 2.809 inches Head Style: Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Oty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Right-hand Thread Length: Between 1.326 inches and 1.386 inches Fastener Length: Between 2.779 inches and 2.809 inches Head Style: Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Thread Length: Between 1.326 inches and 1.386 inches Fastener Length: Between 2.779 inches and 2.809 inches Head Style: Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Between 1.326 inches and 1.386 inches Fastener Length: Between 2.779 inches and 2.809 inches Head Style: Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Fastener Length: Between 2.779 inches and 2.809 inches Head Style: Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thread Dy Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Q-p-35 federal specification single treatment response
Between 2.779 inches and 2.809 inches Head Style: Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Head Style: Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Hexagon Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Head Height: Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Between 0.453 inches and 0.485 inches Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Width Between Flats: Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Between 1.239 inches and 1.252 inches Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Thread Diameter: 0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
0.875 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Min. Tensile Strength (psi): 140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
140000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Material: Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Iron alloy 660 Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Material Specification: Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Ams 5732 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Qq-p-35 federal specification single treatment response
Thread Series Designator:
oad conso 200.g.nateri
Unjf
Specification Data:
80205-nas1014 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0