

View Online at <https://aerobasegroup.com/nsn/5305-00-020-3623>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.361 inches

**Fastener Length:**

Between 2.202 inches and 2.232 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.220 inches and 0.230 inches

**Head Height:**

Between 0.220 inches and 0.280 inches

**First Diameter From Head:**

Between 0.135 inches and 0.145 inches

**Second Diameter From Head:**

Between 0.220 inches and 0.230 inches

**Third Diameter From Head:**

Between 0.091 inches and 0.097 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

1.139 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.219 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.856 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072 finish e300 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.