NSN 5305-00-020-9841

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-020-9841 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.265 inches and 0.334 inches **Fastener Length:** Between 0.964 inches and 1.011 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.677 inches and 0.697 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 300000 pounds per square inch Hardness Rating: 55.0 rockwell c and 58.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel **Material Specification:** Vanadium alloy m-a, vanadium alloys steel co mfr ref single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5305-00-020-9841

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0