NSN 5305-00-020-9842

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-020-9842 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.393 inches and 0.460 inches **Fastener Length:** Between 1.903 inches and 1.950 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.752 inches and 0.762 inches **Grip Diameter:** Between 0.3733 inches and 0.3742 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 300000 pounds per square inch Hardness Rating: 55.0 rockwell c and 58.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel **Material Specification:** Vanadium alloy m-a, vanadium alloys steel co mfr ref single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unj

Ch.

Shelf Life:

N/a

NSN 5305-00-020-9842

Close Tolerance Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0