## NSN 5305-00-020-9967

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-020-9967 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.190 inches and 0.210 inches **Fastener Length:** Between 4.670 inches and 4.690 inches **Head Style:** Double chamfer **Head Diameter:** 0.312 inches **Head Height:** Between 0.150 inches and 0.170 inches **First Diameter From Head:** 0.166 inches **Second Diameter From Head:** 0.156 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 3.920 inches and 3.940 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 4.470 inches and 4.490 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-020-9967

Externally Relieved Body Screw - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A003b0