## NSN 5305-00-021-2578

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-021-2578

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.330 inches
Fastener Length:
6.260 inches
Head Style:
Flat chamfer
Head Diameter:
0.250 inches
Head Height:
0.300 inches
Shoulder Diameter:
0.187 inches first shoulder
Shoulder Length:
5.570 inches first shoulder and 5.590 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
23.0 rockwell c and 32.0 rockwell c
Shoulder Shape:
Round all shoulders
Special Features:
3rd shoulder 0.172 in. Diameter by 0.250 in. Lg, 4th shoulder 0.116 in. Diameter 0.029 in. Lg, 5th shoulder 0.187 in. Diameter by 0.041 in. Lg
Material:
Steel comp 416
Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Thread Series Designator:
Unc

N/a

Shelf Life:

## NSN 5305-00-021-2578

Shoulder Screw - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.