NSN 5305-00-021-3214

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-021-3214 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.110 inches and 0.130 inches **Fastener Length:** Between 0.490 inches and 0.510 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.202 inches and 0.222 inches **Head Height:** Between 0.070 inches and 0.090 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.360 inches and 0.400 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 **Material Specification:** Mil-s-5059 military specification 1st material response or mil-s-7720 military specification 2nd material response **Surface Treatment:** Paint and primer **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

NSN 5305-00-021-3214

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5059 spec.