NSN 5305-00-021-3221

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-021-3221 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.190 inches and 0.210 inches **Fastener Length:** Between 1.020 inches and 1.040 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.380 inches **Head Height:** Between 0.110 inches and 0.130 inches **First Diameter From Head:** Between 0.120 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.810 inches and 0.850 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Painted area gray enamel f-86 type 2 class 3 grade 2 96214 Material: Steel comp 301 or steel comp 302 **Material Specification:** Mil-s-5059 military specification 1st material response or mil-s-7720 military specification 2nd material response **Surface Treatment:** Paint and primer **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-021-3221

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.