## NSN 5305-00-021-3676

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-021-3676 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.308 inches and 0.453 inches **Fastener Length:** Between 0.594 inches and 0.656 inches **Head Style: Button Head Diameter:** Between 0.427 inches and 0.447 inches **Head Height:** Between 0.089 inches and 0.099 inches **Locking Feature:** Pellet **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response **Screw Surface Treatment:** Oxide film **Screw Surface Treatment Specification:** Mil-c-5541 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0

## NSN 5305-00-021-3676

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.