## NSN 5305-00-021-7789

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-021-7789

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.270 inches
Fastener Length:
Between 3.313 inches and 3.353 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.3737 inches and 0.3742 inches
Head Height:
Between 0.253 inches and 0.273 inches
Locking Feature:
Pellet threads
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.076 inches all holes and 0.086 inches all holes
Internal Drive Style:
Hexagon
Thread Diameter:
Thread Diameter: 0.250 inches
0.250 inches
0.250 inches Grip Length:
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches
0.250 inches <b>Grip Length:</b> Between 2.875 inches and 2.895 inches <b>Width Across Flats:</b>
0.250 inches <b>Grip Length:</b> Between 2.875 inches and 2.895 inches <b>Width Across Flats:</b> 0.188 inches
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi):
0.250 inches <b>Grip Length:</b> Between 2.875 inches and 2.895 inches <b>Width Across Flats:</b> 0.188 inches <b>Thready Qty Per Inch (tpi):</b> 28
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center:
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.204 inches all holes and 3.244 inches all holes
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.204 inches all holes and 3.244 inches all holes Material:
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.204 inches all holes and 3.244 inches all holes Material: Stainless steel
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.204 inches all holes and 3.244 inches all holes Material: Stainless steel Surface Treatment:
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.204 inches all holes and 3.244 inches all holes Material: Stainless steel Stainless steel Surface Treatment: Passivate
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.204 inches all holes and 3.244 inches all holes Material: Stainless steel Surface Treatment: Passivate Thread Series Designator:
0.250 inches Grip Length: Between 2.875 inches and 2.895 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 3.204 inches all holes and 3.244 inches all holes Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unf

---

## NSN 5305-00-021-7789

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

