

View Online at <https://aerobasegroup.com/nsn/5305-00-022-7539>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.240 inches and 0.260 inches

Fastener Length:

Between 0.680 inches and 0.700 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.285 inches and 0.332 inches

First Diameter From Head:

Between 0.125 inches and 0.130 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.420 inches and 0.460 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.