Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-022-8321



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.196 inches and 0.294 inches

Fastener Length:

Between 0.281 inches and 0.312 inches

Head Style:

Round

Head Diameter:

Between 0.287 inches and 0.309 inches

Head Height:

Between 0.107 inches and 0.120 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.305 inches and 0.320 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.018 inches and 0.023 inches

Material:

Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1566 primary washer.

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-022-8321

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

