

View Online at <https://aerobasegroup.com/nsn/5305-00-022-8353>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.174 inches and 0.294 inches

**Fastener Length:**

Between 0.281 inches and 0.312 inches

**Head Style:**

Round

**Head Diameter:**

Between 0.334 inches and 0.359 inches

**Head Height:**

Between 0.123 inches and 0.137 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.365 inches and 0.381 inches

**Primary Washer Style:**

Flat external teeth

**Primary Washer Material Thickness:**

Between 0.018 inches and 0.024 inches

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1055 or steel comp 1060

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0