

View Online at <https://aerobasegroup.com/nsn/5305-00-025-7249>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.156 inches

Fastener Length:

3.063 inches

Head Style:

Hexagon extended washer

Head Height:

0.625 inches

Width Between Flats:

Between 0.615 inches and 0.627 inches

Extended Washer Diameter:

1.903 inches

Extended Washer Thickness:

0.187 inches

Hole Diameter:

0.070 inches

Point Length:

0.125 inches

Point Diameter:

Between 0.539 inches and 0.549 inches

Point Style:

Flat

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.625 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Hole Configuration Style:

Hexagon flats

Point Chamfer Angle:

45.0 degrees

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.