Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-026-6547

Throad	Class:
3a	
	Direction:
Right-h	
-	l Length:
	n 1.224 inches and 1.406 inches
	er Length:
	en 1.359 inches and 1.406 inches
Head S	
Flat cha	
	Diameter:
	en 0.863 inches and 0.875 inches
Head H	
	en 0.616 inches and 0.625 inches
	iameter:
0.064 ii	
	I Drive Style:
Hexago	-
	Diameter:
0.625 ii	
Width	Across Flats:
0.500 ii	nches
Hole Q	uantity:
4	
Hole T	ype:
Drilled	
Thread	ly Qty Per Inch (tpi):
11	
Min. Te	ensile Strength (psi):
160000	pounds per square inch
Hardne	ess Rating:
36.0 ro	ckwell c and 43.0 rockwell c
Minimu	Im Yield Strength:
130000	pounds per square inch
Hole C	onfiguration Style:
Round	internal hexagon
Produc	st Name:
	pecial project
Materia	al:
Steel	
	al Specification:
66 fede	ral standard single material response

# NSN 5305-00-026-6547

Socket Head Cap Screw - Page 2 of 2



Surface Treatment:

Zinc

### Surface Treatment Specification:

Qq-z-325, type 2, cl 3 federal specification single treatment response

#### Thread Series Designator:

Unc

# **Specification Or Standard:**

1 type

## Departure From Cited Designator:

As modified by fastener length and head hole configuration

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A003b0