NSN 5305-00-026-6552

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-026-6552 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.438 inches **Fastener Length:** Between 3.594 inches and 3.656 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.863 inches and 0.875 inches **Head Height:** Between 0.616 inches and 0.625 inches **Hole Diameter:** 0.064 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: 0.500 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Hole Configuration Style:** Round internal hexagon **Product Name:** Screw, cap, socket head Material: Steel

Material Specification:

66 federal standard single material response

NSN 5305-00-026-6552

Socket Head Cap Screw - Page 2 of 2



Surrace Treatment:
Zinc
Surface Treatment Specification:
Qq-z-325, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Specification Or Standard:
1 type
Departure From Cited Designator:
As modified by fastener length and head hole configuration
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003h0