## NSN 5305-00-027-5902

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-027-5902 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.156 inches **Fastener Length:** 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.069 inches and 0.079 inches **First Diameter From Head:** 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.344 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response or mil-w-52263 military specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:** 

## NSN 5305-00-027-5902

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-w-52263 spec.