Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-027-5924

2a Thread Direction: Right-hand Thread Length: O.281 inches Fastener Length: 1.281 inches Head Style: Knurled no. 1 Head Diameter: 0.312 inches Head Height: 0.312 inches Head Height: 0.312 inches First Diameter From Head: 0.033 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: 0.968 inches Thread Quarter From Head: 0.908 inches Thread Diameter: 0.968 inches Thread Diameter: 0.978 inches Thread Diameter: 0.988 inches Thread Diameter: 0.988 inches Thread Strive Edody Diameter Quartity: 1 Material: State content: 1 Material: State content: Passivate Thread Strive Deosignator: Unc	
Thread Direction: Right-hand Thread Length: 0.281 inches Fastener Length: 1.281 inches Head Syle: Numed no. 1 Head Syle: 0.312 inches Head Height: 0.312 inches Head Height: 0.312 inches Head Height: 0.312 inches Head Height: 0.312 inches Head Diameter: 0.312 inches Distance From Head: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.096 inches Internal Drive Style: Sol Thread Quarter: 0.328 inches Thread Diameter: 0.318 inches Thread Diameter: 0.328 inches Streace Teatment: Sulface Teatment: Sulface Stell Sulface Teatment: Pasivate Thread Sries Designator: Unc Sulface Teatment: Pasivate	Thread Class:
Right-hand Thread Length: 0.281 inches Fastener Length: 1.281 inches Head Style: Knurdel no. 1 Head Diameter: 0.312 inches Head Height: 0.312 inches First Diameter From Head: 0.033 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.039 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.039 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.039 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches Thread Vity Per Inch (tpl): 32 Zeternality Relieved Body Diameter Quantity: 1 Material: Stall Less teol Starless teol	
Thread Length: 0.281 inches Fastene Length: 1.281 inches Head Style: Kourled no. 1 Head Diameter: 0.312 Inches Head Pight: 0.312 Inches Head Height: 0.312 Inches Head Height: 0.312 Inches First Diameter From Head: 0.033 Inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.036 Inches Internal Drive Style: Otto 1015 Netad Diameter: 0.138 Inches Thread Diameter: 0.138 Inches Thread Diameter: 0.138 Inches Thread Diameter: 0.138 Inches Thread Diameter: 0.138 Inches State Externality Relieved Body Diameter Quantity: 1 Material: Staties steel Surface Tostment: Passivate Thread Staties Consignator: Internal Consignator: Internal Consignator:	
0.281 inches Fastener Length: I.281 inches I.281 inches Head Style: Kourled no. 1 Head Diametor: 0.312 inches Head Height: 0.312 inches IHerad Height: 0.312 inches IFirst Diameter From Head: 0.312 inches IFirst Diameter From Head: 0.309 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.398 inches Internal Drive Style: Stot Internal Drive Style: Stot Internal Drive Style: 1 Stot Internal Parelexee Body Diameter Quantity: I Stot Internal Relieved Body Diameter Quantity: I Stot Internal Relieved Body Diameter Quantity: I Stot Internal Stotes Internal Relieved Body Diameter Quantity: I Stot Internal Stotes Internal IN Stotes I	
Fastener Length: 1.281 inches Head Style: Knurled no. 1 Head Diameter: 0.312 inches Head Height: 0.312 inches First Diameter From Head: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.096 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thread V Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Starles steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Unit Of Measure: Cu Domiliarization: Na Surface Treatment: Surface Designator: Unit Of Measure: Surface Designator: Surface Treatment: Surfac	
1.281 inches Head Style: Knurled no. 1 Head Indeton. 1 Head Indeton. 1 Head Indeton. 1 Head Style: 0.312 inches Bad Height: 0.312 inches First Diameter From Head: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.096 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches Thread Vt Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stanless steel Surfaces Tread Series Designator: Unc Starless Steel Dread Series Designator: Unc Sheft Life: Na Unit Of Measure: Tor Demiliatization: Na Sheft Life: Na Sheft Life: Na Sheft Life: Na Desid Nameter	
Head Style: Knurled no. 1 Head Diameter: 0.312 Inches Head Height: 0.312 Inches Fist Diameter From Head: 0.093 Inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.998 Inches Internal Drive Style: Slot Thread Diameter: 0.138 Inches Thready Qt Per Inch (tpi): 32 Sustance Treatment: Sustance Treatment: Sustance Treatment: Sustance Treatment: Sustance Treatment: Sustances Steel Surface Treatment: Passivate Interd Series Designator: Unc Shell Life: Na Materia: Data Series Sustance: Display Thread Series Designator: Unc Shell Life: Na Dimiliarization: Na Fig:	
Knitled no. 1 Head Diameter: 0.312 Inches Head Height: 0.312 Inches Head First Diameter From Head: 0.933 Inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 Inches Internal Drive Style: Stot Thread Diameter: 0.138 Inches Thready Qty Per Inch (tpl): 32 State Statesteal Staternally Relieved Body Diameter Quantity: 1 Material: Statesteal Statesteal <	
Head Diameter: 0.312 inches Head Height: 0.312 inches First Diameter From Head: 0.030 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches Thread Vip Per Inch (tpl): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shef Life: Na Thread Series Designator: Unc Shef Life: Na Fig:	Head Style:
0.312 inches Head Height: 0.312 inches First Diameter From Head: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thread Y Per Inch (tpl): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Sheft Life: Na Unit Of Measure: - Demilitarization: No Fig:	Knurled no. 1
Head Height: 0.312 inches First Diameter From Head: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thread Q ty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Staties steel Surface Treatment: Passivate Thread Series Designator: Unc Shef Life: Na Unit Of Measure:	Head Diameter:
0.312 inches First Diameter From Head: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thread Diameter: 0.138 inches Thread Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shef Liffe: N/a Unc Fineal Series Designator: N/a	0.312 inches
First Diameter From Head: 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shef Life: N/a Unt Of Measure: - - Penilitarization: No Fig:	Head Height:
0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Din Of Measure: Demilitarization: No Fig:	0.312 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.968 inches Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Sheff Life: Na Unc Sheff Life: Na Din Of Measure: Demilitarization: No Fig:	First Diameter From Head:
0.968 inches Internal Drive Style: Stot Thread Diameter: 0.138 inches 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: 1 Material: Stainless steel Sturface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.093 inches
Internal Drive Style: Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Slot Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Sheff Life: Na Unc Denilitarization: Passivate Fig:	0.968 inches
Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Material: Stainless steel Stainless steel Stainless steel Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Sheff Life: Na Unit Of Measure: Demilitarization: No Fig:	Internal Drive Style:
0.138 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No	Slot
Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Diameter:
32 Externally Relieved Body Diameter Quantity: 1 Material: Material: Stainless steel Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	0.138 inches
Externally Relieved Body Diameter Quantity: 1 1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: - Demilitarization: No Fig:	Thready Qty Per Inch (tpi):
1 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	32
Material:Stainless steelSurface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Externally Relieved Body Diameter Quantity:
Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Pemilitarization: No	1
Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Stainless steel
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Passivate
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
	Filg:
A003b0	A003b0