NSN 5305-00-031-1136

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-031-1136 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.317 inches **Fastener Length:** Between 0.698 inches and 0.745 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.296 inches and 0.301 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp 4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:**

Unjf
Shelf Life:
N/a
Unit Of Measure:
--

NSN 5305-00-031-1136

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0