## NSN 5305-00-032-4119

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-032-4119 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.330 inches **Fastener Length:** Between 0.830 inches and 0.850 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.180 inches Width Between Flats: Between 0.302 inches and 0.322 inches **First Diameter From Head:** Between 0.110 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.400 inches and 0.480 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm as82 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 2 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-032-4119

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.