NSN 5305-00-034-1382

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-034-1382

| View Online at https://aerobasegroup.com/nsn/5305-00-034-1382 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.316 inches |
| Fastener Length: |
| Between 0.739 inches and 0.769 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.442 inches |
| Internal Drive Style: |
| Torque set |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ams 5737 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A500d0 |