NSN 5305-00-034-2608



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-034-2608 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.265 inches and 0.328 inches **Fastener Length:** Between 0.781 inches and 0.812 inches **Head Style:** Fillister **Head Diameter:** Between 0.287 inches and 0.309 inches **Head Height:** Between 0.106 inches and 0.113 inches **Hole Diameter:** 0.046 inches First Diameter From Head: Between 0.109 inches and 0.116 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.484 inches and 0.516 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 **Hole Configuration Style: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 416 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5305-00-034-2608

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0