## NSN 5305-00-036-6902

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-036-6902 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.558 inches and 0.620 inches **Fastener Length:** 0.620 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.085 inches and 0.096 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** Between 0.305 inches and 0.320 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.018 inches and 0.023 inches Material: Steel comp 1115 fastener or steel comp 1132 fastener or steel comp 1010 fastener or steel comp 1020 fastener **Material Specification:** Aisi assn standard single material response primary washer **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-036-6902

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0