Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-036-6905

| Thread Class:   |
|---|
| 2a  |
| Za<br>Thread Direction:   |
|   |
| Right-hand  |
| Thread Length:<br>Between 0.217 inches and 0.230 inches                   |
|   |
| Fastener Length:<br>Between 0.279 inches and 0.310 inches                 |
|   |
| Head Style:<br>Pan no. 2  |
| Head Diameter:  |
|   |
| Between 0.357 inches and 0.373 inches                                     |
| Head Height:  |
| Between 0.099 inches and 0.110 inches                                     |
| Washer Quantity:  |
|   |
| Internal Drive Style:   |
| Slot  |
| Thread Diameter:  |
| 0.190 inches  |
| Thready Qty Per Inch (tpi):   |
| 24  |
| Primary Washer Outside Diameter:  |
| Between 0.365 inches and 0.381 inches                                     |
| Primary Washer Style:   |
| Flat external teeth   |
| Primary Washer Material Thickness:  |
| Between 0.018 inches and 0.024 inches                                     |
| Material:   |
| Steel   |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

## NSN 5305-00-036-6905

Assembled Washer Screw - Page 2 of 2

**Fiig:** A003b0

