NSN 5305-00-036-6923

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-036-6923 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.380 inches **Fastener Length:** Between 0.385 inches and 0.432 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Hole Diameter:** Between 0.032 inches and 0.042 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.052 inches and 0.072 inches **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round **Surface Finish:** 63.0 microinches grip Material: Titanium alloy **Material Specification:** Nas 621, 6al-4v assn standard single material response **Thread Series Designator:** Unjf

Specification Data:

26512-gb511j manufacturers standard

NSN 5305-00-036-6923

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0