NSN 5305-00-038-1604

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-038-1604 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.276 inches **Fastener Length:** Between 0.323 inches and 0.370 inches **Head Style:** Round **Head Diameter:** Between 0.258 inches and 0.278 inches **Head Height:** Between 0.074 inches and 0.086 inches **Grip Diameter:** Between 0.1365 inches and 0.1375 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches **Grip Length:** Between 0.047 inches and 0.077 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch **Surface Finish:** 32.0 microinches grip Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 4140 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification all treatment responses **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-038-1604

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0