NSN 5305-00-038-1918

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-038-1918 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.246 inches and 0.323 inches **Fastener Length:** Between 2.011 inches and 2.058 inches **Head Style:** Pan **Head Diameter:** Between 0.361 inches and 0.381 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.735 inches and 1.765 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Surface Finish: 32.0 microinches grip Steel comp 4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-038-1918

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0