# NSN 5305-00-038-2431

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-038-2431



## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 1.194 inches and 1.318 inches

#### Fastener Length:

Between 1.313 inches and 1.375 inches

#### Head Style:

Flat countersunk

## Head Diameter:

Between 0.233 inches and 0.279 inches

## Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.138 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

125000 pounds per square inch

## Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Product Name:**

Navy special project

#### Screw Material:

Steel comp 8630 or steel comp 4037

## Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

## Screw Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification all treatment responses

#### **Special Features:**

Finish black color, 65-b-cd

## **Thread Series Designator:**

Unjc

## Specification Data:

80205-nas514 professional/industrial association standard

## Shelf Life:

N/a

# NSN 5305-00-038-2431

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

