Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-038-3103



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.407 inches and 0.500 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.085 inches and 0.096 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Primary Washer Outside Diameter:

Between 0.305 inches and 0.320 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.018 inches and 0.023 inches

Material Specification:

66 federal standard all material responses primary washer

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5305-00-038-3103

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

