NSN 5305-00-038-3150

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-038-3150 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.766 inches and 0.880 inches **Fastener Length:** Between 0.849 inches and 0.880 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.099 inches and 0.110 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Primary Washer Outside Diameter:** Between 0.365 inches and 0.381 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.018 inches and 0.024 inches Material: Steel **Material Specification:** Sae assn standard all material responses or aisi assn standard all material responses or 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc

__

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-038-3150

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0