NSN 5305-00-038-8898

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-038-8898 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.260 inches and 0.328 inches **Fastener Length:** Between 0.296 inches and 0.328 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Color: Black Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 1 military specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-00-038-8898

Socket Head Cap Screw - Page 2 of 2



Ini	1 (Of	ΝЛ	മാ	e i	ırc	٠.

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.