

View Online at <https://aerobasegroup.com/nsn/5305-00-038-9411>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.420 inches and 0.430 inches

Fastener Length:

Between 1.472 inches and 1.502 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.367 inches and 0.375 inches

Head Height:

Between 0.133 inches and 0.150 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Grip Length:

Between 1.052 inches and 1.072 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

120000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4140 fastener or steel comp e4340 fastener or steel comp 8740 fastener

Material Specification:

Mil-s-5626 military specification 1st material response fastener or mil-s-5000 military specification 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas1184 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.