## NSN 5305-00-040-9226

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-040-9226

| Thread Class:                    |  |
|----------------------------------|--|
| 2a                               |  |
| Thread Direction:                |  |
| Right-hand                       |  |
| Thread Length:                   |  |
| Between 0.907 inches and 1.00    | 0 inches   |
| Fastener Length:                 |  |
| Between 0.969 inches and 1.00    | 0 inches   |
| Head Style:                      |  |
| Pan                              |  |
| Head Diameter:                   |  |
| Between 0.357 inches and 0.37    | 3 inches   |
| Head Height:                     |  |
| Between 0.122 inches and 0.13    | 3 inches   |
| Locking Feature:                 |  |
| Patch threads or pellet threads  | or strip threads   |
| Internal Drive Style:            |  |
| Cross recess type 1              |  |
| Thread Diameter:                 |  |
| 0.190 inches                     |  |
| Thready Qty Per Inch (tpi):      |  |
| 32                               |  |
| Min. Tensile Strength (psi):     |  |
| 55000 pounds per square inch     |  |
| Material:                        |  |
| Steel                            |  |
| Material Specification:          |  |
| Astm a108 assn standard single   | e material response or qq-s-637 federal specification single material response or 66 federal standard single |
| material response                |  |
| Surface Treatment:               |  |
| Cadmium and chromate             |  |
| Surface Treatment Specificati    | on:  |
| Qq-p-416, type 2, cl 3 federal s | pecification all treatment responses   |
| Thread Series Designator:        |  |
| Unf                              |  |
| Specification Or Standard:       |  |
| 3 type and 9c style              |  |
| Shelf Life:                      |  |
| N/a                              |  |
| Unit Of Measure:                 |  |
|                                  |  |
| Demilitarization:                |  |
| No                               |  |

## NSN 5305-00-040-9226

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

