NSN 5305-00-040-9354

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-040-9354 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.886 inches and 1.019 inches **Fastener Length:** Between 1.063 inches and 1.125 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unjf **Specification Data:** 80205-nas514 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-040-9354

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.