NSN 5305-00-040-9447

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-040-9447 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.441 inches and 0.508 inches **Fastener Length:** Between 2.076 inches and 2.123 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.081 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 2.009 inches first hole Material: Stainless steel **Thread Series Designator:** Unjf **Specification Data:** 08524-b-19019 manufacturers standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-040-9447

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0