

View Online at <https://aerobasegroup.com/nsn/5305-00-040-9684>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.437 inches and 0.516 inches

**Fastener Length:**

Between 1.828 inches and 1.875 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.327 inches and 0.385 inches

**Locking Feature:**

Patch or pellet or strip threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Navy special project

**Material:**

Steel comp 4037 or steel comp 8630

**Material Specification:**

Ams 6300 assn standard 14th material response or mil-s-6050 military specification 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6050 spec.