

View Online at <https://aerobasegroup.com/nsn/5305-00-040-9758>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.395 inches and 0.415 inches

**Fastener Length:**

Between 0.473 inches and 0.483 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.052 inches and 0.072 inches

**Width Between Flats:**

0.219 inches

**Shoulder Diameter:**

0.135 inches first shoulder and 0.145 inches first shoulder

**Shoulder Length:**

0.068 inches first shoulder and 0.078 inches first shoulder

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Shoulder Shape:**

Round first shoulder

**Material:**

Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0