

View Online at <https://aerobasegroup.com/nsn/5305-00-041-8702>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.719 inches

**Fastener Length:**

1.750 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.841 inches and 0.875 inches

**Head Height:**

0.281 inches

**Internal Drive Style:**

Torque

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 25.0 rockwell c and 29.0 rockwell c

**Screw Material:**

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

**Screw Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Screw Surface Treatment:**

Cadmium

**Screw Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6758 spec.