NSN 5305-00-042-0441

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-0441 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** 0.438 inches **Head Style:** Round **Head Diameter:** Between 0.217 inches and 0.236 inches **Head Height:** Between 0.083 inches and 0.095 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.125 inches Thready Qty Per Inch (tpi): 40 **Hardness Rating:** 40.0 rockwell c and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.258 inches and 0.268 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.016 inches Material: Steel comp 1010 or steel comp 1050 or steel comp 1566 or steel **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-042-0441

Assembled Washer Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0