## NSN 5305-00-042-0454

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-0454 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Round **Head Diameter:** Between 0.240 inches and 0.260 inches **Head Height:** Between 0.091 inches and 0.103 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.278 inches and 0.288 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.018 inches Material: Steel or steel comp 1010 or steel comp 1050 or steel comp 1566 **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-042-0454

Assembled Washer Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0