NSN 5305-00-042-0988

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-0988 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.153 inches and 0.289 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Round **Head Diameter:** Between 0.443 inches and 0.472 inches **Head Height:** Between 0.160 inches and 0.175 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 40.0 rockwell c and 50.0 rockwell c **Primary Washer Outside Diameter:** Between 0.460 inches and 0.475 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-042-0988

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0