## NSN 5305-00-042-0991

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-0991 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.369 inches and 0.469 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Round **Head Diameter:** Between 0.443 inches and 0.472 inches **Head Height:** Between 0.160 inches and 0.175 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Primary Washer Outside Diameter:** Between 0.460 inches and 0.475 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches Material: Steel fastener **Material Specification:** Sae assn standard single material response primary washer **Surface Treatment:** Zinc primary washer **Surface Treatment Specification:** Qq-z-325, type 1, cl 3 federal specification single treatment response primary washer **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-042-0991

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0