

View Online at <https://aerobasegroup.com/nsn/5305-00-042-0994>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.716 inches and 0.852 inches

Fastener Length:

0.875 inches

Head Style:

Round

Head Diameter:

Between 0.443 inches and 0.472 inches

Head Height:

Between 0.160 inches and 0.175 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.460 inches and 0.475 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.023 inches and 0.028 inches

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp 1054 or steel comp 1055 or steel comp 1059 or steel comp 1060 or steel comp 1561 or steel comp 1566

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0