NSN 5305-00-042-3435

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-3435 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.375 inches **Head Style:** Round **Head Diameter:** Between 0.443 inches and 0.472 inches **Head Height:** Between 0.160 inches and 0.175 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.466 inches and 0.478 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.025 inches Material: Steel comp 1010 or steel comp 1050 or steel comp 1566 **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

NSN 5305-00-042-3435

Assembled Washer Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0