NSN 5305-00-042-3522

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-3522 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.387 inches and 0.484 inches **Fastener Length:** 0.500 inches **Head Style:** Hexagon **Head Height:** Between 0.067 inches and 0.080 inches Width Between Flats: Between 0.244 inches and 0.250 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.270 inches and 0.285 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.016 inches and 0.020 inches Material: Steel **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-00-042-3522

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0