NSN 5305-00-042-3535

Shelf Life:

N/a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-3535 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.384 inches and 0.482 inches **Fastener Length:** 0.500 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.305 inches and 0.312 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.305 inches and 0.320 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.018 inches and 0.023 inches Material: Steel **Material Specification:** Sae assn standard all material responses **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc

NSN 5305-00-042-3535

Assembled Washer Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0