
Assembled Washer Screw - Page 1 of 2





## **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.386 inches and 0.469 inches Fastener Length: Between 0.469 inches and 0.500 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.312 inches Washer Quantity: **Internal Drive Style:** Torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Primary Washer Outside Diameter:** Between 0.365 inches and 0.381 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.020 inches and 0.025 inches Material: Steel comp 1010 or steel comp 1020 or steel comp 1050 **Material Specification:** Sae assn standard all material responses Surface Treatment: Cadmium or zinc Surface Treatment Specification: Qq-p-416, type 1, class 3 federal specification 1st treatment response or qq-z-325, type 1, class 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a

1

Unit Of Measure:

---

## NSN 5305-00-042-3545

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

