Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-042-3568



## **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.469 inches and 0.594 inches Fastener Length: Between 0.594 inches and 0.625 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.552 inches and 0.562 inches Washer Quantity: 1 **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Primary Washer Outside Diameter:** Between 0.640 inches and 0.660 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.032 inches and 0.040 inches Material: Steel comp 1010 or steel comp 1020 or steel comp 1050 Material Specification: Sae assn standard all material responses Surface Treatment: Cadmium or zinc Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

Unit Of Measure:

---

## NSN 5305-00-042-3568

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

